

TRENCHERS|ZC-M|S|H|R|X

SKID STEER LOADERS SSL | COMPACT TRACK LOADERS | COMPACT WHEEL LOADERS
COMPACT BACKHOE LOADERS | TELEHANDLERS
BACKHOE LOADERS | EXCAVATORS

POWERATTACHMENTS®

TDI

www.tdimentos.com



High performance trenchers with different chains available, for trench opening in all vegetable terrains, mixed and compact grounds, even very hard soils or with roots.

FEATURES

- Transmission through hydraulic motor with planetary gearbox to chain.
- Lateral sideshift with mechanical adjust.
- One or two spreading augers.
- Trench cleaner with spring loaded crumbrer
- Available three chain versions.
- Hydraulical connections for Skid Steer Loader. P+T.
- ISO 24410 attach frame type Skid Steer Loader.

OPTIONS

- NO ISO Attach frame for Compact loader. ENOSSLU.
- Attach frame for telehandlers, backhoe-loaders and wheel loaders ETHBLWL.
- Bracket for excavators. EEXCVTR.

TRENCHERS | ZC-M | S | H | R | X

SKID STEER LOADERS SSL | COMPACT TRACK LOADERS | COMPACT WHEEL LOADERS
 COMPACT BACKHOE LOADERS | TELEHANDLERS
 BACKHOE LOADERS | EXCAVATORS

POWERATTACHMENTS



www.tdimentos.com

MODEL		ZC-090M	ZC-090S	ZC-120H
MAXIMUM DEPTH	mm	900	900	900
AVAILABLE WIDTHS	cm	10 15 20	10 15 20	10 15 20 25 30
CHAIN PITCH	inch	1.5/8"	1.5/8"	1.5/8"
SPOIL AUGER	#	1	1	2
RECOMMENDED FLOW	lpm	38 ~ 76	49 ~ 83	49 ~ 76
MAXIMUM PRESSURE	bar	242	242	242
APPROXIMATE WEIGHT	kg	240	300	340



AVAILABLE CHAINS

EARTH	MIXED	ROCKY
FEATURES <ul style="list-style-type: none"> • For soft clean grounds, with standard blades in 50% of the chain stations. • For ZC-090M S models. 	FEATURES <ul style="list-style-type: none"> • For hard grounds, with standard & tungsten blades (30% 70%). • For ZC-###M S H R X models. 	FEATURES <ul style="list-style-type: none"> • For very hard grounds, with tungsten blades in all chain stations. • For ZC-###M S H R X models.

REPLACEMENT BLADES

CZ-DER1 CZ-IZQ1	ZZ-DER1 CEN1 IZQ1	CZ-DER2 CZ-IZQ2	ZZ-DER2 CEN2 IZQ2
FEATURES <ul style="list-style-type: none"> • Standard blade: 1.5/8" right left. • Weight: 0.26 kg. 	FEATURES <ul style="list-style-type: none"> • Tungsten blade: 1.5/8" right center left. • Weight: 0.25 kg. 	FEATURES <ul style="list-style-type: none"> • Standard blade: 2" right left. • Weight: 0.32 kg. 	FEATURES <ul style="list-style-type: none"> • Tungsten blade: 2" right center left. • Weight: 0.30 kg.

TRENCHERS | ZC-M | S | H | R | X

SKID STEER LOADERS SSL | COMPACT TRACK LOADERS | COMPACT WHEEL LOADERS
 COMPACT BACKHOE LOADERS | TELEHANDLERS
 BACKHOE LOADERS | EXCAVATORS

POWERATTACHMENTS
TDI
 www.tdimentos.com

MODEL		ZC-120R	ZC-150R	ZC-120X
MAXIMUM DEPTH	mm	1200	1500	1200
AVAILABLE WIDTHS	cm	10 15 20 25 30	10 15 20 25 30	10 15 20 25 30 35
CHAIN PITCH	inch	2"	2"	2"
SPOIL AUGER	#	1	1	2
RECOMMENDED FLOW	lpm	57 ~ 114	106 ~ 174	57 ~ 114
MAXIMUM PRESSURE	bar	242	242	242
APPROXIMATE WEIGHT	kg	425	485	500



AVAILABLE CHAINS

MIXED



FEATURES

- For hard grounds, with standard & tungsten blades (30%|70%).
- For ZC-###M | S | H | R | X models.

ROCKY



FEATURES

- For very hard grounds, with tungsten blades in all chain stations.
- For ZC-###M | S | H | R | X models.

REPLACEMENT BLADES

CZ-DER1 | CZ-IZQ1



FEATURES

- Standard blade: 1.5/8" right | left.
- Weight: 0.26 kg.

ZZ-DER1 | CEN1 | IZQ1



FEATURES

- Tungsten blade: 1.5/8" right | center | left.
- Weight: 0.25 kg.

CZ-DER2 | CZ-IZQ2



FEATURES

- Standard blade: 2" right | left.
- Weight: 0.32 kg.

ZZ-DER2 | CEN2 | IZQ2



FEATURES

- Tungsten blade: 2" right | center | left.
- Weight: 0.30 kg.